

EFFECT OF ADDITIVE ON THE MEMBRANE PERFORMANCE
AND MEMBRANE STRUCTURE

WONG LING YONG

FAKULTI SAINS DAN TEKNOLOGI
LEJ UNIVERSITI SAINS DAN TEKNOLOGI MALAYSIA

2005

EFFECT OF ADDITIVE ON THE MEMBRANE PERFORMANCE AND
MEMBRANE STRUCTURE

By

Wong Ling Yong

Research report submitted in partial fulfillment of
the requirements for the degree of
Bachelor of Science (Environmental Technology)

Department of Engineering Sciences
Faculty of Science and Technology
KOLEJ UNIVERSITI SAINS DAN TEKNOLOGI MALAYSIA
2005

Ketua Jabatan Sains Kejuruteraan:

Nama: Pn. Ir Ahmad bin Jamil

Cop Ramai:

Tarikh:.....

4
46
FST
5
2005

1100036928



JABATAN SAINS KEJURUTERAAN
FAKULTI SAINS DAN TEKNOLOGI
KOLEJ UNIVERSITI SAINS DAN TEKNOLOGI MALAYSIA

PENGAKUAN DAN PENGESAHAN LAPORAN
PROJEK PENYELIDIKAN I DAN II

Adalah ini diakui dan disahkan bahawa laporan penyelidikan bertajuk:

EFFECT OF ADDITIVE ON THE MEMBRANE PERFORMANCE AND MEMBRANE STRUCTURE

oleh WONG LING YONG

No. Matrik UK 6552 telah diperiksa dan semua pembetulan yang disarankan telah dilakukan. Laporan ini dikemukakan kepada Jabatan Sains Kejuruteraan sebagai memenuhi sebahagian daripada keperluan memperolehi Ijazah SARJANA MUDA TEKNOLOGI (ALAM SEKITAR), Fakulti Sains dan Teknologi, Kolej Universiti Sains dan Teknologi Malaysia.

Disahkan oleh:

Penyelia Utama

Nama: Dr Nora'aini binti Ali

DR. NORA'AINI BINTI ALI

Cop Rasmi:

Pensyarah
Jabatan Sains Kejuruteraan
Fakulti Sains dan Teknologi
Kolej Universiti Sains dan Teknologi Malaysia
21030 Kuala Terengganu.

17.04.05

Tarikh:.....

Penyelia Kedua(jika ada)

Nama: Encik Asmadi bin Ali @ Mahmud

ASMAIDI BIN ALI @ MAHMUD

Cop Rasmi:

Pensyarah
Jabatan Sains Kejuruteraan
Fakulti Sains dan Teknologi
Kolej Universiti Sains dan Teknologi Malaysia
21030 Kuala Terengganu

17/04/05

Tarikh:.....

Ketua Jabatan Sains Kejuruteraan

Nama: PM.Ir Ahmad bin Jusoh

Cop Rasmi:

17/04/05

Tarikh:.....

ACKNOWLEDGEMENT

Glory to the Lord! Thanks for providing wisdom and encouragement all the way in accomplishing this final year project!

Writer wishes to express the deepest gratitude to the supervisor, Dr. Nora'aini, and co-supervisor, Mr Asmadi Ali, not forgotten also to Mr Zul as an external advisor for their guidance during the laboratory work and also thesis writing.

Next, writer wishes to thank all lab assistants, especially Miss Mazalina, Mrs Siti Zulaika, Mr Razman, Mr Mahmud , and Mr Zaki from Environmental Engineering Department for their cooperation and their help during the laboratory work., and also not forgotten, Mr Rozali who help in SEM process for the membranes.

Besides that, writer also would like to thank every friend in membrane group for thesis, 2004/2005 especially Mr Edwin, Mr Willibrord, Mr Murugan, Mr Khairul Fazrie, and Miss Shazana for their advice and assistance all the time when needed.

Finally, thanks for those who are involved, either direct or indirectly in this final year project. May God bless you all!

Ketua Jurutera Sains Keterwakil

Nama: P.M.Y Ahmad bin Jusoh

Coy: Rizwak

Tarikh: 10/10/2005

CONTENTS

	PAGE
TITLE PAGE	i
APPROVAL FORM	ii
ACKNOWLEDGEMENTS	iii
TABLE OF CONTENTS	iv
LIST OF TABLES	vii
LIST OF FIGURES	ix
LIST OF ABBREVIATIONS/SYMBOLS	xi
LIST OF APPENDICES	xii
ABSTRACT	xiii
ABSTRAK	xiv

CHAPTER 1 INTRODUCTION AND OBJECTIVES

1.1 Introduction	1
1.2 Problem Statement	3
1.3 Research Objectives	3
1.4 Scopes Research	4

CHAPTER 2 LITERATURE REVIEW

2.1	Asymmetric Membrane and Dry/Wet Phase Inversion	5
2.2	Polyethersulfone (PES)	6
2.3	<i>N</i> -methyl-2-pyrrolidinone (NMP)	8
2.4	Water	9
2.5	Polyvinylpyrrolidone (PVP)	11
2.6	Permeability, Pure Water Flux and Salt Flux	14

CHAPTER 3 METHODOLOGY

3.1	Dope Preparation/ Material Selection	16
3.2	Preparation of Polymer Solution (Ternary System)	17
3.3	Titration Method	19
3.4	Preparation of dope formulation or casting solution (Quaternary System)	21
3.5	Fabrication of Polyethersulfone Flat Sheet Membrane	22
3.6	Share Rate	24
3.7	Scanning Electron Microscopy (SEM)	24
3.8	Membrane Performance Testing	25
3.9	Dilution of Salt	31
3.10	Stock Solution Dilution	32

CHAPTER 4 RESULT AND DISCUSSION

4.1 Pure Water Flux Measurement	35
4.2 Comparison among the Produced Membrane by Salt Water Rejection	37
4.3 Comparison among the Produced Membranes by their Structures	44

CHAPTER 5 CONCLUSION AND RECOMMENDATIONS

5.1 Conclusion	48
5.2 Recommendation	50

REFERENCES 52

APPENDIX 54

VITAE CURRICULUM 60

LIST OF TABLES

TABLE		PAGE
3.1	Table shows the composition for every chemical for each membrane (Ternary system)	18
3.2	Table shows the weight of dope for each solution used for titration	20
3.3	Table shows amount of water needed to achieve cloud point for each solution	20
3.4	Table shows the actual composition for each chemical in dope for titration	20
3.5	Table shows the composition for quaternary system solution	21
3.6	Table shows the solute radius and diffusivity of each ions and solute	31
3.7	Table shows the obtained values of diffusion coefficient for selected salts	31
3.8	Table shows the dilution table for Salt Solution	32
3.9	Table shows linear equation for calibration curve of conductivity versus concentration	34

TABLE	PAGE
-------	------

4.1	Table shows permeability coefficient for membrane with different concentration of PVP	37
4.2	Table show salt water flux produced by membranes with the pressure given (10-18 bar)	40
4.3	Table shows percentage of rejection by membranes with the pressure given (10-18 bar)	42

LIST OF FIGURES

FIGURE		PAGE
2.1	Figure show molecular structure for polyethersulfone	6
2.2	Figure show molecular structure for polyvinylpyrrolidone	11
3.1	Figure shows apparatus set up for solution preparation	18
3.2	Figure shows apparatus set up for titration method	19
3.3	Figure shows the semi automated casting machine	23
3.4	Figure shows a formed thick film membrane in coagulation bath	23
3.5	Figure shows Scanning Electron Microscopy apparatus set up	25
3.6	Figure shows Sterlitech stirred cell (dead end operation) placed on the magnetic stirrer magnetic stirrer	26
4.1	Graft shows comparison among pure water flux produced with pressure given for membrane with concentration of PVP 5 wt.% ($y = 1.098 \times 10^{-7}x$, $R^2 = 0.9482$), 7 wt.% ($y = 2.055 \times 10^{-7}x$, $R^2 = 0.9693$), and 9 wt.% ($y = 4.475 \times 10^{-7}x$, $R^2 = 0.9984$)	36

FIGURE	PAGE
---------------	-------------

- | | | |
|-----|--|----|
| 4.2 | Graft shows the comparison of flux produced with pressure given (12-20 bar) for NaCl rejection among membranes with different concentration of PVP | 38 |
| 4.3 | Graft shows comparison of rejection with pressure given (12-20 bar) for NaCl rejection among membranes with different concentration of PVP | 41 |
| 4.4 | Graft shows comparison of rejection with flux for NaCl rejection among membranes with different concentration of PVP | 43 |
| 4.5 | Figure shows Scanning electron micrographs of membrane cross section with: (a) 5 wt% PVP, (b) 7 wt.% PVP, and (d) 9 wt.% PVP. | 45 |

LIST OF ABBREVIATIONS / SYMBOLS

INOS	Institute of Oceanography
NaCl	Sodium Chloride
NF	Nanofiltration
NMP	<i>N</i> -methyl-2-pyrrolidinone
PES	Polyethersulfone
PSF	Polysulfone
PVP	Polyvinylpyrrolidone
RO	Reverse Osmosis
SEM	Scanning Electron Microscopy
UF	Ultrafiltration

LIST OF APPENDICES

APPENDIX

- A Schematic set up for permeation test
- B Calculation for preparing the casting solution of 100 mL for Ternary System
- C Graft of Conductivity versus Concentration
- D Calculation for preparation for Stock Solution 0.01 M
- E Table of result for rejection test
- F Graft for water flux against pressure (salt water rejection)

ABSTRACT

In order to prepare high performance of membrane filtration, an experiment using quaternary system was carried out with widely used membrane - Polyethersulfone (PES) as polymer, *N*-methyl-2-pyrrolidinone (NMP) as solvent, water as non-solvent, and polyvinylpyrrolidone (PVP) as additive. Water was used as coagulation bath and methanol as post treatment. In this study, effect of additive concentration on the membrane performance was studied. By undergoing this study, effect of additive can be identified in order to improve membrane performance. Three membranes with different additive concentrations (5 wt.%, 7 wt.%, and 9 wt.%) were tested to find out the flux produced and rejection to the salt water by each membrane. The method used was wet phase inversion. The results obtained shows that the membrane with 9 wt.% of PVP produced the most flux than the others. Flux produced was in a range between 4.231×10^{-6} m/s and 6.301×10^{-6} m/s. Meanwhile, the highest rejection for salt water was obtained by membrane with 7 wt.% of additive, which reject in a range between 53% and 60%. Morphology of each membrane was studied using Scanning Electron Microscopy (SEM). Structure of membrane had shown that membrane with PVP concentration of 7 wt.% was having more well formed finger like structure and macro voids formation than the one with 5 wt.% and 9 wt.%.

ABSTRAK

Untuk membolehkan penghasilan membran penuras yang berpretasi tinggi, satu eksperimen menggunakan sistem kuaternari telah dijalankan dengan menggunakan membran yang luas penggunaannya - Polyethersulfone (PES) sebagai polimer, *N*-methyl-2-pyrrolidinone (NMP) sebagai pelarut, air sebagai bukan pelarut, dan polyvinylpyrrolidone (PVP) sebagai aditif. Air telah digunakan sebagai larutan pengental dan metanol sebagai rawatan lanjutan. Dalam kajian ini, kesan aditif terhadap membran telah dikaji. Dengan menjalani kajian ini, kesan aditif dapat dikenalpasti dan membantu dalam peningkatan mutu membran. Tiga membran dengan kandungan editif berlainan (5 wt.%, 7 wt.%, dan 9 wt.%) masing-masing telah dikaji untuk mengetahui kebolehan dalam penghasilan fluks dan penyingkiran garam. Cara yang digunakan dalam proses ini ialah fasa balikan basah. Keputusan yang didapat menunjukkan membran dengan PVP 9 wt.% telah menghasilkan fluks yang terbanyak jika dibanding dengan yang lain. Fluks yang dihasilkan adalah dalam lingkungan 4.231×10^{-6} m/s dan 6.301×10^{-6} m/s. Manakala penyingkiran garam yang terbanyak ialah membran dengan kandungan PVP 7 wt.%, dalam lingkungan 53% dan 60%. Morfologi setiap membran turut dikaji menggunakan pengimbas elektron mikroskopik (SEM). Struktur membran yang diperhati menunjukkan bahawa membran yang mengandungi PVP 7 wt.% menghasilkan struktur jejari dan lompong makro yang lebih sempurna daripada membran yang mengandungi PVP 5 wt.% dan PVP 9 wt.%.